

## BCS BLIND CONTRACT SYSTEM INSTALL INSTRUCTIONS

BY SIMPLY FOLLOWING THESE STEP-BY-STEP INSTRUCTIONS, YOU WILL SOON BE ENJOYING YOUR NEW BLINDS.

### Getting Started:

Please read through all instructions carefully before you begin installation.

Unpack all materials making sure all components are included:

- Assembled BCS rail with motor
- Mounting brackets
- Remote Control
- Counterweight, optional

Please note that your brackets must be securely attached to the mounting surface. If your screws do not hit wood studs you'll have to use a different fastener, which can be found at any local hardware store.

### Tools You Will Need:

- Drill with a 1/8" bit and a Phillips bit
- Phillips screwdriver
- Metal tape measure

### Installing Your Blind Contract System:

You are now ready to install your blind hardware.

#### Wall Mount:

- 1. Measure**  
Measure from the first cord roll support to the last cord roll support for width of brackets.
- 2. Mark**  
Mark the height you would like the top of blind rail to be installed.
- 3. Attach Bracket**  
Attach your brackets to your desired area. Drill screws through holes for a secure mount. Tracks hold 6 lbs/ft. Support brackets occur every 4 feet.
- 4. Attach Track**  
Insert track onto bracket applying pressure until track "clicks" into place.
- 5. Optional Counterweight**  
Slide counterweight into bottom hem pocket.
- 6. Program Remote**  
Use the instruction sheet included with your remote for programming. If you need assistance, please call Seabrook at 800-238-9152.

#### Ceiling Mount:

- 1. Measure**  
Rails are pre-assembled to your specified size.
- 2. Attach Bracket**  
Attach bracket to ceiling by first pre-drilling holes for screw diameter when mounting into a ceiling stud. Otherwise, pre-drill and install anchors first before fastening with screws. Tracks hold 6 lbs/ft. Support brackets occur every 4 feet.
- 3. Attach Track**  
Insert track onto bracket applying pressure until track "clicks" into place.
- 4. Optional Counterweight**  
Slide counterweight into bottom hem pocket.
- 5. Program Remote**  
Use the instruction sheet included with your remote for programming. If you need assistance, please call Seabrook at 800-238-9152.